

FIBER OPTIC PIGTAILS



FEATURES

- Low insertion Loss and High Return Loss
- Excellent endface geometry parameter
- Varieties of connectors SC, LC ST, FC, E2000
- Excellent polished and 100% tested.
- Good repeatability and exchangeability

APPLICATION

- Optical Fiber Communication System
- Optical Access Network
- Optical Fiber CATV
- FTTX
- Optical Test Instruments

TECHNICAL SPECIFICATIONS

Fiber Type	Single Mode G652D, G657A1/A2/B2/B3	Multimode OM1, OM2, OM3, OM4, OM5
Connector Type	SC, LC ST, FC, E2000, MU or others	
Cable Jacket	LSZH. PVC	
Return Loss	UPC \geq 50dB APC \geq 60 dB	\geq 30 dB
Insertion Loss		\leq 0.3 dB
Repeatability		\leq 0.1 dB 1000 Times
Inter changeability		\leq 0.2 dB
Durability		\leq 0.2 dB 1000 Times
Operating Temperature		-40°C ~ +80°C

PART NUMBER GENERATOR

INTELPL/---/---/---	Fiber Type: <i>SM Single Mode G652D/SMA1 - Single Mode G657A1/ SMA2 - Single Mode G657A2 OM1 - Multimode OM1/ OM2 - Multimode OM2/ OM3 - Multimode OM3/OM4 - Multimode OM4</i>
	Connector Type: <i>SC, LC ST, FC, E2000, MU or others</i>
	Length: <i>1 Meter/ 2 Meter/ 3 Meter</i>
INTELPLSMSC1	Single mode SC Pigtail 1 meter