


FIBER OPTIC PATCHCORDS



FEATURES

- Low insertion Loss and High Return Loss
- Excellent endface geometry parameter
- Varieties of connectors SC, LC ST, FC, E2000
- Excellent polished and 100% tested.
- Good repeatability and exchangeability

APPLICATION

- Optical Fiber Communication System
- Optical Access Network
- Optical Fiber CATV
- FTTX
- Optical Test Instruments

TECHNICAL SPECIFICATIONS

Fiber Type	Single Mode G652D, G657A1/A2/B2/B3	Multimode OM1, OM2, OM3, OM4, OM5
Connector Type	SC, LC ST, FC, E2000, MU or others	
Cable Type	Duplex, Simple, Armoured	
Cable Jacket	LSZH. PVC. PE	
Return Loss	UPC ≥ 50dB APC ≥ 60 dB	≥ 30 dB
Insertion Loss		≤ 0.3 dB
Repeatability		≤ 0.1 dB 1000 Times
Inter Change		≤ 0.2 dB
Durability		≤ 0.2 dB 1000 Times
Operating Temperature		-40°C ~ +80°C

PART NUMBER GENERATOR

INTELPD/---/---/---	Fiber Type: <i>SM- Single Mode G652D/SMA1 - Single Mode G657A1/ SMA2 - Single Mode G657A2</i> <i>OM1 - Multimode OM1/ OM2 - Multimode OM2/ OM3 - Multimode OM3/OM4 - Multimode OM4</i>
	Connector Type: <i>SC, LC ST, FC, E2000, MU or others</i>
	Cable Type: <i>D- Duplex/S-Simples/R- Armoured</i>
	Length: <i>1 Meter/ 2 Meter/ 3 Meter</i>
INTELPDSMSCSCD1	Single mode SC-SC Duplex Patchcord 1 meter